



SCAN TO LEARN MORE ABOUT THIS TRAILER

MAKE	GVWR (LBS)	TRAILER DIMENSIONS	MAX REEL DIMENSIONS	AXLE	REEL BAR DIA.
Brindle	52,000	45' L x 8' 6" W	(5) 96" or (4) 120" D x 77" W	Tri-Axle, Dual Wheels	3"

Our wind farm reel trailers come equipped with larger tires to help you navigate your heavy cable across rough or sandy terrain. The wider stance build of these five reel trailers allows (5) 8,800lb reels and provides more stability as you move down your line tensioning.

UNIT DETAILS

- 3" ADJUSTABLE REEL BARS WITH COLLARS
- 12,000LB HD FRONT JACK
- (2) REAR STABILIZING JACKS
- LED LIGHTS
- ELECTRIC TRAILER BRAKES
- 7-WAY ROUND TRAILER PLUG
- ADJUSTABLE PINTLE HITCH
- MULTI-REEL INNERDUCT TRAILER
- ADJUSTABLE REEL POSITIONS

TRIPLEXING MV CABLE WRAPPER

The Triplexing MV Cable Wrapper can save on material, labor, and time when compared to zip-ties. Wrap up to 2 miles per hour, engineered to wrap MV cable in a triplex bundle using twine. The Triplexing MV Cable Wrapper is self-propelled and requires no additional power sources.

- Save up to 60% in wrapping/tie labor costs.
- Save up to 80% on wrapping/tie materials.

