

## LCT-7500 Cable Trailer

The LCT 7500 comes standard with a Figure 8 Assembly for different types of fiber cable, including ribbon fiber. The unit is powered by a 20 HP Honda engine and a two-stage hydraulic system for high speed or high torque, and includes one arbor with a set of bushings and lock collars for a single reel, auxiliary quick couplers for operating hydraulic tools, and a tension brake. This trailer has a 7,500 lb. payload capacity and is equipped with (2) 6,000 lb. Dexter Torflex Axles. Figure-8 up to 750' per minute.



### TRAILERS EQUIPPED WITH

Max Reel 7,500lbs and 120" x 60" Width  
 Auxiliary Hydraulic Ports  
 20HP Honda Engine  
 Hydraulic Flow Rate of 12GPM at 2000PSI  
 Figure-8 and Rewind Cable up to 750FPM  
 Swinging Control Panel at the rear of the trailer  
 Hydraulic Lifting Rack

### EQUIPMENT SPECIFICATIONS

Galvanized  
 Dual Axle, Single Wheels

GVWR	TRAILER	MAX PAYLOAD	MAX REEL DIMENSIONS	REEL BAR DIA	HYDRAULICS	SPEED
12,000 lbs	8' Width x 14' Length	7,500 lbs	120" Diameter x 60" Width	2"	12GPM at 2000 psi	750' /min

