



SLRT 8108-8KE

HYDRAULIC REEL TRAILER



SCAN TO LEARN MORE ABOUT THIS TRAILER

LOAD CAP. (LBS)	GVWR (LBS)	OVERALL LENGTH	OVERALL MAX WIDTH	REEL SIZE
6,500	9,400	134"	101"	(1) 96" D x 60" W X 3" Center Hole

AXLE

- AXLE: 7,000 LBS SINGLE TORSION AXLE
- TIRES: (2) 215/75R17.5 LR-H TIRES

REEL RACK

- TWIN 4" LIFT CYLINDERS, LEVER CONTROLLED
- HEAVY DUTY BRONZE BUSHINGS
- (2) 7/8" REEL BARS W/CROSS ARMS/LOCKING

HYDRAULIC TAKE UP/PAYOUT

- DIRECT DRIVE TO REEL BAR
- 2,100 LBS OF LINE PULL ON 24" DRUM @ 1.8K PSI

POWER PACK

- 14 HP KOHLER GAS ENGINE W/ELECTRIC START
- 20 GAL RESERVOIR
- 10 MICROPIN SPIN ON FILTER
- 2,250 PSI CONTINUOUS
- 2,900 PSI INTERMITTENT
- 8 GPM

TENSIONING BRAKE ASSEMBLY

- 16" X 3/4 ALUMINUM BRONZE DISK BRAKES
- 10,000 LBS OF CLAMPING FORCE

ADDITIONAL INFO

- (2) 1/2" PINTLE HITCH
- PAIR OF WHEEL CHOCKS INCLUDED